



12724 (ZW3005)

**Z-Wave, In-Wall Smart Dimmer
(Interchangeable Paddles)**



Key Features

- Turn ON/OFF and control the brightness level of the connected lighting manually or via Z-Wave remote control.
- May be used in single pole installation or with up to four GE model 12723 Add-on switches in 3, 4, 5 or 6-way wiring configurations
- UL Listed to work with dimmable LED & CFLs
- Blue LED indicates switch location in a dark room
- Can be Included in multiple Groups and Scenes
- Supports Advanced Configuration; Dim rates, LED status, Invert switch (if unit is installed upside down)
- Screw Terminal installation; requires wiring connections for Line (Hot), Load, Neutral and Ground. Traveler wire required for multi pole installation
- Use a standard-size wall plate for single gang installations (wall plate not included); Multi-gang box option available (removable 'side wings')
- Interchangeable Paddle switch: White & light almond paddle included in package
- LED can be enabled/disabled manually
- Inline traveler circuit protection

SPECIFICATIONS

Power: 120 VAC, 60 Hz.

Signal (Frequency): 908.42 MHz.

Maximum Load: 600W, incandescent; 150W Dimmable CFL/LED

Operating Temperature Range: 32-104° F (0-40° C)

For indoor use only. Not for use with appliance or motors

cUL Listed

Complies with FCC and Industry Canada regulations

JASCO Products

10 E. Memorial Rd

Oklahoma City, OK 73114

www.jascopeproducts.com

Z-Wave is a registered US trademark of Sigma Designs

The GE logo is a registered trademark of General Electric Company and is used under license to JASCO products Company, LLC

The images, product information and specifications listed in this document are subject to change